



SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/9

20% Winter Windscreen Wash

Revision 15

Revision date 2021-05-04

1.1. Product identifier

Product name 20% Winter Windscreen Wash

Product code QAFS026-20%

1.2. Relevant identified uses of the substance or mixture and uses advised against

Product Use [SU22] Professional uses: Public domain (administration, education, entertainment, services,

craftsmen); [PC35] Washing and cleaning products (including solvent based products);

Description Screenwash for Vehicles.

1.3. Details of the supplier of the safety data sheet

Company Superfine Manufacturing Ltd

Address Orchardbank Industrial Estate

Forfar Angus Scotland DD8 1TD

 Web
 www.superfine.co.uk

 Telephone
 Tel: 01307 463538

 Fax
 Fax: 01307 468505

Email address of the competent person

nigel@superfine.co.uk

1.4. Emergency telephone number

Emergency telephone number

01307 463538

8.30am to 17.00pm

For medical advice or information you should contact your GP or NHS 111 (or NHS 24 in

Scotland) on 111 (for 24 hour health advice)

If you are a healthcare professional with an enquiry please visit www.TOXBASE.org

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.2. Classification - EC 1272/2008

Flam. Liq. 3: H226; Eye Irrit. 2: H319;

2.2. Label elements

Hazard pictograms





Signal Word

Warning

Hazard Statement

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Revision 15 Revision date 2021-05-04

2.2. Label elements

	Eye Irrit. 2: H319 - Causes serious eye irritation.
Precautionary Statement:	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
Prevention	smoking.
	P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement:	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
Response	lenses, if present and easy to do. Continue rinsing.
	P337+P313 - If eye irritation persists: Get medical advice/attention.
Precautionary Statement:	P403+P235 - Store in a well-ventilated place. Keep cool.
Storage	
Precautionary Statement:	P501 - Dispose of contents/container to an approved disposal site, in accordance with local
Disposal	regulations.
SUPPLEMENTAL HAZARD	Ingredients as required by Regulation (EC) No 648/2004:.
INFORMATION	20% Denatured Ethanol, Less than 5% Anionic Surfactants, Less than 5% Non-ionic Surfactants,
	CI 42090.

2.3. Other hazards

Other hazards	This mixture is not classified as PBT or vPvB according to current EU criteria.
---------------	---

SECTION 3: Composition/information on ingredients

3.2. Mixtures

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration	Conc.	Classification
				Number	(%w/w)	
Ethanol: Ethyl Alcohol (Ethanol)		64-17-5	200-578-6	01-2119457610-43	10 - 20%	Flam. Liq. 2: H225; Eye Irrit. 2: H319;
methanol	603-001-00-X	67-56-1	200-659-6	01-2119433307-44	0.5 - 1%	Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370;

Further information

Product Shelf Life	RECOMMENDED SHELF LIFE 1 YEAR FROM DATE OF DELIVERY.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move the exposed person to fresh air.
Eye contact	Rinse immediately with plenty of water. Contact lenses should be removed.
Skin contact	Remove contaminated clothing. Wash with water and soap as a precaution.
Ingestion	DO NOT INDUCE VOMITING. Rinse mouth thoroughly.

4.2. Most important symptoms and effects, both acute and delayed

4.2. Most important symptoms and effects, both acute and delayed			
Inhalation	High concentration of vapour in enclosed space may cause irritation, headaches and nausea. May		
	cause irritation to respiratory system.		
Eye contact	Causes serious eye irritation.		
Skin contact	May cause skin dryness and irritation. Prolonged contact may cause defatting of the skin.		
Ingestion	May cause irritation to mucous membranes.		

4.3. Indication of any immediate medical attention and special treatment needed

	TREAT SYMPTOMATICALLY.
Inhalation	Move the exposed person to fresh air. Seek medical attention if irritation or symptoms persist.
Eye contact	Contact lenses should be removed. Rinse immediately with plenty of water. Seek medical attention if irritation or symptoms persist.
Skin contact	Seek medical attention if irritation or symptoms persist.
Ingestion	Drink 1 to 2 glasses of water. Seek medical attention if irritation or symptoms persist.

Revision 15 Revision date 2021-05-04

General information	
	If you feel unwell, seek medical advice (show the label where possible). Treat symptomatically.
SECTION 5: Firefighting mea	asures
5.1. Extinguishing media	
, ,	Flammable liquid. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
5.2. Special hazards arising from	n the substance or mixture
	Flammable liquid and vapour.
5.3. Advice for firefighters	
	Fire fighters should wear self contained positive pressure breathing apparatus (SCBA) and full turnout gear.
Further information	
	In the event of a fire and/or explosion do not breath fumes. Standard procedure for chemical fires. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
SECTION 6: Accidental relea	ase measures
6.1. Personal precautions, prote	ctive equipment and emergency procedures
	Wear suitable protective equipment. Flammable liquid. Avoid sparks, flames, heat and sources of ignition.
6.2. Environmental precautions	
	Advise local authorities if large spills cannot be contained.
6.3. Methods and material for co	ontainment and cleaning up
	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Avoid sparks, flames, heat and sources of ignition.
6.4. Reference to other sections	
	See section 2, 7, 8, 13 for further information.
SECTION 7: Handling and st	torage
7.1. Precautions for safe handling	ng engles en
	Adopt best Manual Handling considerations when handling, carrying and dispensing.
7.2. Conditions for safe storage,	including any incompatibilities
	Flammable liquid. Avoid sparks, flames, heat and sources of ignition. Avoid storing in direct Sun Light. Store in a well-ventilated place. Keep cool. Store in original container. Keep container tightly closed. Keep away from combustible material. Keep out of the reach of children.
7.3. Specific end use(s)	
	Screenwash for Vehicles.
Suitable packaging	
	Plastic containers.
SECTION 8: Exposure contr	ols/personal protection
8.1. Control parameters	
	Occupational exposure controls.
8.1.1. Exposure Limit Values	

Revision 15 Revision date 2021-05-04

8.1.1. Exposure Limit Values

Ethanol: Ethyl Alcohol (Ethanol)	WEL 8-hr limit ppm: 1000	WEL 8-hr limit mg/m3: 1920
, , ,	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
methanol	WEL 8-hr limit ppm: 200	WEL 8-hr limit mg/m3: 266
	WEL 15 min limit ppm: 250	WEL 15 min limit mg/m3: 333
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:
Monopropylene Glycol	WEL 8-hr limit ppm: -	WEL 8-hr limit mg/m3: 10
(Propane-1,2-diol particulates)	NATEL AE main limit manne.	NATEL AE main limit mantage.
	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
Monopropylene Glycol	respirable dust: WEL 8-hr limit ppm: 150	respirable dust: WEL 8-hr limit mg/m3: 474
(Propane-1,2-diol total vapour	WEL 6-III IIIIII ppiii. 190	WEL 6-III IIIIII IIIIg/III3. 474
and particulates)		
and particulation	WEL 15 min limit ppm: -	WEL 15 min limit mg/m3: -
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	inhalable dust:	inhalable dust:
	WEL 8-hr limit mg/m3 total -	WEL 15 min limit mg/m3 total -
	respirable dust:	respirable dust:

DNEL: Derived no-effect level.

Exposure Pattern - Workers

Ethanol: Ethyl Alcohol	Long-term - inhalation - Systemic	950 mg/m³		
,	effects	· ·		
	Long-term - inhalation - Local	1900 mg/m ³	Long-term - dermal - Systemic	343 mg/kg
	effects		effects	
methanol	Acute inhalation - Systemic	260 mg/m ³		
	effects			
	Acute inhalation - Local effects	260 mg/m ³	Acute dermal - Systemic effects	40 mg/kg
	Long-term - inhalation - Systemic	260 mg/m ³	Long-term - inhalation - Local	260 mg/m ³
	effects		effects	
	Long-term - dermal - Systemic	40 mg/kg		
	effects			
Monopropylene Glycol	Long-term - inhalation - Systemic	168 mg/m³		
	effects			
	Long-term - inhalation - Local	10 mg/m³		
	effects			

Exposure Pattern - General population

Revision 15 Revision date 2021-05-04

Exposure Pattern - General population

Ethanol: Ethyl Alcohol	Long-term - inhalation - Systemic	114 mg/m³		
	effects			
	Long-term - inhalation - Local	950 mg/m³	Long-term - dermal - Systemic	206 mg/kg
	effects		effects	
	Long-term - oral - Systemic	87 mg/kg		
	effects			
methanol	Acute inhalation - Systemic	50 mg/m³		
	effects			
	Acute inhalation - Local effects	50 mg/m³	Acute dermal - Systemic effects	8 mg/kg
	Long-term - inhalation - Systemic	50 mg/m³	Long-term - inhalation - Local	50 mg/m³
	effects		effects	
	Long-term - dermal - Systemic	8 mg/kg		
	effects			
Monopropylene Glycol	Long-term - inhalation - Systemic	50 mg/m³		
	effects			
	Long-term - inhalation - Local	10 mg/m³	Long-term - dermal - Systemic	213 mg/m ³
	effects		effects	
	Long-term - oral - Systemic	85 mg/m³		
	effects			

8.2. Exposure controls





Adopt best Manual Handling considerations when handling, carrying and dispensing. Avoid contact with skin and eyes. Handle in accordance with good industrial hygiene and safety practice. Use appropriate personal protective equipment. Wear suitable protective clothing and eye/face protection.

8.2.1. Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapours below there respective threshold limit value. Ensure eyewash stations and safety showers are close to the workstation location.

Eye / face protection

Avoid contact with eyes. If splashes are likely to occur, wear: safety glasses with side-shields. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Wear chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Skin protection - Handprotection

Rubber gloves. Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer.

No personal respiratory protective equipment normally required. In case of insufficient ventilation

Respiratory protection

wear suitable respiratory equipment.

Prevent further leakage or spillage if safe to do so.

8.2.3. Environmental exposure controls

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Revision 15 Revision date 2021-05-04

9.1. Information on basic physical and chemical properties

Appearance Liquid Colour Blue Odour Characteristic No data available Odour threshold 7.5 - 8.9 pН Melting point No data available Initial boiling point No data available Flash point 36 °C No data available **Evaporation rate** Flammability (solid, gas) No data available Vapour pressure No data available Vapour density No data available Relative density No data available Partition coefficient No data available Autoignition temperature No data available Viscosity < 50 centipoise No data available **Explosive properties** Oxidising properties No data available Solubility No data available

9.2. Other information

Conductivity
Surface tension
Specific gravity
Gas group
Benzene Content
Lead content
VOC (Volatile organic compounds)
No data available

SECTION 10: Stability and reactivity

10).1	١.	Rea	ctiv	/ity

Flammable liquid. Stable under normal conditions.

10.2. Chemical stability

Flammable liquid. Stable under normal conditions.

10.3. Possibility of hazardous reactions

Oxidising agents. Combustible materials.

10.4. Conditions to avoid

Avoid sparks, flames, heat and sources of ignition. Avoid storing in direct Sun Light.

10.5. Incompatible materials

Oxidising agents. Combustible materials.

10.6. Hazardous decomposition products

No Hazardous decomposition products when stored and handled correctly.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in Regulation (EC) No 1272/2008 (CLP).

Revision 15 Revision date 2021-05-04

	10000011 4410 2021 00 0			
11.1. Information on toxicologica	al effects			
Acute toxicity	based on available data the classification criteria are not met.			
	Oral ATE = >10,000 mg/kg.			
	Dermal ATE = >10,000 mg/kg.			
	Inhalation - Vapours ATE = 83.33 mg/l.			
Skin corrosion/irritation	based on available data the classification criteria are not met.			
Serious eye damage/irritation	Eye Irrit. 2: H319 - Causes serious eye irritation.			
Respiratory or skin sensitisation	based on available data the classification criteria are not met.			
Germ cell mutagenicity	based on available data the classification criteria are not met.			
Carcinogenicity	based on available data the classification criteria are not met.			
Reproductive toxicity	based on available data the classification criteria are not met.			
STOT-single exposure	based on available data the classification criteria are not met.			
STOT-repeated exposure	based on available data the classification criteria are not met.			
Aspiration hazard	based on available data the classification criteria are not met.			
Repeated or prolonged	based on available data the classification criteria are not met.			
exposure				
11.1.2. Mixtures				
	No data available.			
11.1.3. Hazard Information				
	No data available.			
11.1.4. Toxicological Information	n			
	No data available			
SECTION 12: Ecological info	ormation			
12.1. Toxicity				
	No data available			
12.2. Persistence and degradab	ility			
	Substance biodegrades at a moderate rate and inherently biodegradable according to the OECD guide lines.			
12.3. Bioaccumulative potential	10			
	The product is not bioaccumulating.			
Partition coefficient				
	20% Winter Windscreen Wash No data available Ethanol: Ethyl Alcohol -0.35 log P Monopropylene Glycol -1.07 log P methanol -0.82			
12.4. Mobility in soil				
	This product is soluble in water.			
12.5. Results of PBT and vPvB	assessment			
	This mixture is not classified as PBT or vPvB according to current EU criteria.			
12.6. Other adverse effects				
	No data available.			
SECTION 13: Disposal cons	siderations			
13.1. Waste treatment methods				
	Dispose of waste and residues in accordance with local authority requirements.			
	•			

Revision 15

	Revision 1:
General information	Revision date 2021-05-04
	Dispess of in compliance with all lead and national requirements
Dianocal of packaging	Dispose of in compliance with all local and national requirements.
Disposal of packaging	D NOT
	Do NOT reuse empty containers. Empty containers can be sent to landfill after cleaning, if in compliance with local and national regulations.
SECTION 14: Transport info	
Hazard pictograms	
	3
14.1. UN number	
	UN1170
14.2. UN proper shipping name	
	ETHANOL SOLUTION
14.3. Transport hazard class(es	;)
ADR/RID	3
Subsidiary risk	Ţ ₋
IMDG	3
Subsidiary risk	-
IATA	3
Subsidiary risk	-
14.4. Packing group	1
Packing group	111
14.5. Environmental hazards	
Environmental hazards	No
Marine pollutant	No
14.6. Special precautions for us	ser
	no additional special precautions.
14.7. Transport in bulk according	ng to Annex II of MARPOL 73/78 and the IBC Code
	Not applicable.
ADR/RID	
Hazard ID	30
Tunnel Category	(D/E)
IMDG	·
EmS Code	F-E S-D
IATA	-
Packing Instruction (Cargo)	366
Maximum quantity	220 L
Packing Instruction	355
(Passenger)	
Maximum quantity	60 L
Further information	
	Carran Wash Flash Daint 00.000

Screen Wash Flash Point - 36.0 °C.

Revision 15 Revision date 2021-05-04

Further information

DO NOT EXCEED 30 degC for transport.

Special Provision 144 for UN 1170 states An Aqueous Solution containing not more than 24% alcohol by volume is not subject to the requirements of ADR. Therefore this product is not hazardous for transport.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations

REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

15.2. Chemical safety assessment

No information available.

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas:.		
	11 - Repeated or prolonged exposure.		
	14 - ADR/RID.		
	14 - IMDG.		
	14 - IATA.		
	14 - 14.6. Special precautions for user.		
	14 - 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code.		
Data sources	Classification and Procedure used to derive the classification for mixtures according to Regulation		
	(EC) No. 1272/2008:.		
	Flam. Liq. 3: H226 - Flammable liquid and vapour Flash Point - 36 degC.		
	Eye Irrit. 2: H319 - Causes serious eye irritation Calculation Method.		
Text of Hazard Statements in	Flam. Liq. 2: H225 - Highly flammable liquid and vapour.		
Section 3	Eye Irrit. 2: H319 - Causes serious eye irritation.		
	Acute Tox. 3: H301 - Toxic if swallowed.		
	Acute Tox. 3: H311 - Toxic in contact with skin.		
	Acute Tox. 3: H331 - Toxic if inhaled.		
	STOT SE 1: H370 - Causes damage to organs .		

Further information

The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.